

TICAB SP. Z O.O.

35-304, ul. Świętojańska 71B, Rzeszow, Poland

35-322 Spichlerzowa 38C, Rzeszow, Poland

Viber, WhatsApp: +48 (732) 081 224[**ticab.sale@ticabltd.com**](mailto:ticab.sale@ticabltd.com)

STREET VACUUM CLEANER CITYANT

Equipment for cleaning urban areas, streets, sidewalks, parks, stadiums, railway stations, airports, parking lots, industrial areas from different waste.

Street vacuum cleaner CityAnt works on electrical accumulators which provide 9-hour autonomous work. It can be charged in the nighttime from the 220V. Easy-to-push vacuum cleaner can be used by one hand, noiseless.

Changing the trash bag takes only 2-3 minutes. No air pollution.

It can take all the waste: wood, steel, plastic, paper, carton pieces, textile waste, leaves, cigarette butt, cans and bottles (glass, plastic and metal) etc.

CityAnt fits different areas: concrete, asphalt, pavement, lawn, sand, etc.

Technical specifications:

- Electric motor - 48V / 1200W
- Electric drive - enabling forward and reverse travel -
- Waste collector type - hopper;
- Vacuum power 1200W;
- Maximum speed 6 km/h;
- Hopper capacity 240l;
- Vacuum hose Ø 125 mm;
- Vacuum hose length 2,5 m;
- Autonomous work time 8 h;
- Charging time 10-12 h;
- Wheels Ø 320mm;
- Doble nebulizers;
- Dust filter with an area of 16 m²;
- Possibility of overcoming curbs by 15 cm.
- Sprayer: 2 - external and internal.
- Warning lamp



PRICE* – ~~11000~~ 8900 euro netto

* promotional price is valid from 25.11.23 to 30.12.23.

we have in stock

FCA, EXW, Rzeszow, Poland

35-322 Spichlerzowa 38C

Please correspond by e-mail or WhatsApp, Viber

+48(732) 081 224-Mila Shevchuk

The equipment we produce makes driving more comfortable.

Technical characteristics and equipment

| | | |
|--------------------------------------|-------------------------------|---------------|
| Overall dimensions (L*W*H) | mm | 1700x700x2300 |
| Weight in empty state | kg | 468 |
| Type of dust collector | bag (polyethylene), container | |
| Self-propelled (max. width) | km/h | 6 |
| The volume of the garbage tank | L | 240 |
| Protection class | IP | 54 |
| Number of engines | piece | 2 |
| Capacity | kW | 2,5 |
| Noise level | dB | 64,2 |
| Engine protection filter | -- | includes |
| Main filter area | m ² | 5 |
| Charging time | h | 10-12 |
| Wheel size | mm | Ø320,400 |
| Air pressure in the tyres is optimal | bar | 1,5 |
| Filter category | -- | M |
| Nominal vacuum, suction system | kPa | 3,0 |
| Air intake system performance | l/s | 300 |
| Brakes | -- | mechanical |
| Hill climbing ability (max) | degrees. | 10 |

